CS 267 Applications of Parallel Computers

Lecture 18:

Dense Linear Algebra - II

James Demmel

http://www.nersc.gov/~dhbailey/cs267/Lectures/Lect_18_2000.ppt

Review of last lecture and Outline

- Motivation for Dense Linear Algebra (Lectures 10-11)
  - Ax=b: Computational Electromagnetics
  - Ax = λx: Quantum Chemistry
- Review Gaussian Elimination (GE) for solving Ax=b
- Optimizing GE for caches on sequential machines
  - using matrix-matrix multiplication (BLAS)
  - Other BLAS3 important too
- LAPACK library overview and performance
- Data layouts on parallel machines

- Review GE and Data layouts
- Parallel matrix-matrix multiplication
- Parallel Gaussian Elimination
- ScaLAPACK library overview
- Open Problems

BLAS2 version of Gaussian Elimination with Partial Pivoting (GEPP)

```
for i = 1 to n-1
    find and record k where |A(k,i)| = max{i <= j <= n} |A(j,i)|
          … i.e. largest entry in rest of column i
    if |A(k,i)| = 0
        exit with a warning that A is singular, or nearly so
    elseif  k != i
        swap rows i and k of A
    end if
    A(i+1:n,i) = A(i+1:n,i) / A(i,i)
                 … each quotient lies in [-1,1]
                 … BLAS 1
    A(i+1:n,i+1:n) = A(i+1:n , i+1:n ) - A(i+1:n , i) * A(i , i+1:n)
                 … BLAS 2, most work in this line
```

BLAS 3 (Blocked) GEPP, using Delayed Updates

```
for   ib = 1 to n-1 step b      … Process matrix b columns at a time
    end = ib + b-1              … Point to end of block of b columns
    apply BLAS2 version of GEPP to  get A(ib:n , ib:end) = P' * L' * U'
    … let LL denote the strict lower triangular part of A(ib:end , ib:end) + I
    A(ib:end , end+1:n) = LL^-1 * A(ib:end , end+1:n)        … update next b rows of U
BLAS 3 A(end+1:n , end+1:n ) = A(end+1:n , end+1:n )
            - A(end+1:n , ib:end) * A(ib:end , end+1:n)
                                 … apply delayed updates with single matrix-multiply
                                 … with inner dimension b
```

Gaussian Elimination using BLAS 3



Parallelizing Gaussian Elimination

- Recall parallelization steps from Lecture 3
  - **Decomposition:** identify enough parallel work, but not too much
  - **Assignment:** load balance work among threads
  - **Orchestrate:** communication and synchronization
  - **Mapping:** which processors execute which threads
- Decomposition
  - In BLAS 2 algorithm nearly each flop in inner loop can be done in parallel, so with n^2 processors, need 3n parallel steps

```
for i = 1 to n-1
    A(i+1:n,i) = A(i+1:n,i) / A(i,i)          … BLAS 1 (scale a vector)
    A(i+1:n,i+1:n) = A(i+1:n , i+1:n )  … BLAS 2 (rank-1 update)
            - A(i+1:n , i) * A(i , i+1:n)
```

  - This is too fine-grained, prefer calls to local matmuls instead
  - Need to discuss parallel matrix multiplication
- Assignment
  - Which processors are responsible for which submatrices?

Different Data Layouts for Parallel GE (on 4 procs)

Bad load balance: P0 idle after first n/4 steps



1) Column Blocked Layout



2) Column Cyclic Layout

Load balanced, but can't easily use BLAS2 or BLAS3

Can trade load balance and BLAS2/3 performance by choosing b, but factorization of block column is a bottleneck



3) Column Block Cyclic Layout



4) Row and Column Block Cyclic Layout

The winner!

0	1	2	3
1	2	3	0
2	3	0	1
3	0	1	2

5) Block Skewed Layout

Complicated addressing

How to proceed:

- Consider basic parallel matrix multiplication algorithms on simple layouts
  - Performance modeling to choose best one
    - Time (message) = latency + #words * time-per-word
    - $= \alpha + n*\beta$
- Briefly discuss block-cyclic layout
- PBLAS = Parallel BLAS

Parallel Matrix Multiply

- Computing C=C+A*B
- Using basic algorithm: $2*n^3$ Flops
- Variables are:
  - Data layout
  - Topology of machine
  - Scheduling communication

- Use of performance models for algorithm design

1D Layout

- Assume matrices are n x n and n is divisible by p



- A(i) refers to the n by n/p block column that processor i owns (similiarly for B(i) and C(i))
- B(i,j) is the n/p by n/p sublock of B(i)
  - in rows j*n/p through (j+1)*n/p
- Algorithm uses the formula

$$C(i) = C(i) + A*B(i) = C(i) + \sum_{j} A(j)*B(j,i)$$

Matrix Multiply: 1D Layout on Bus or Ring

- Algorithm uses the formula

$$C(i) = C(i) + A*B(i) = C(i) + \sum_{j} A(j)*B(j,i)$$

- First consider a bus-connected machine without broadcast: only one pair of processors can communicate at a time (ethernet)

- Second consider a machine with processors on a ring: all processors may communicate with nearest neighbors simultaneously

Naïve MatMul for 1D layout on Bus without Broadcast

Naïve algorithm:

```
C(myproc) = C(myproc) + A(myproc)*B(myproc,myproc)
for i = 0 to p-1
  for j = 0 to p-1 except i
     if (myproc == i) send A(i) to processor j
     if (myproc == j)
        receive A(i) from processor i
        C(myproc) = C(myproc) + A(i)*B(i,myproc)
     barrier
```

Cost of inner loop:

computation: $2*n*(n/p)^2 = 2*n^3/p^2$

communication: $\alpha + \beta*n^2/p$

Naïve MatMul (continued)

Cost of inner loop:

computation: $2*n*(n/p)^2 = 2*n^3/p^2$

communication: $\alpha + \beta*n^2/p$ … approximately

Only 1 pair of processors (i and j) are active on any iteration,

an of those, only i is doing computation

=> the algorithm is almost entirely serial

Running time: **$(p*(p-1) + 1)*$computation + $p*(p-1)*$communication**

$\sim= 2*n^3 + p^2*\alpha + p*n^2*\beta$

this is worse than the serial time and grows with p

Better Matmul for 1D layout on a Processor Ring

- Proc i can communicate with Proc(i-1) and Proc(i+1) simultaneously for all i

```
Copy A(myproc) into Tmp
C(myproc) = C(myproc) + T*B(myproc , myproc)
for j = 1 to p-1
    Send Tmp to processor myproc+1 mod p
    Receive Tmp from processor myproc-1 mod p
    C(myproc) = C(myproc) + Tmp*B( myproc-j mod p , myproc)
```

- Same idea as for gravity in simple sharks and fish algorithm
- Time of inner loop = $2*(\alpha + \beta*n^2/p) + 2*n*(n/p)^2$
- Total Time = $2*n*(n/p)^2 + (p-1) *$ Time of inner loop
  $\sim 2*n^3/p + 2*p*\alpha + 2*\beta*n^2$

- Optimal for 1D layout on Ring or Bus, even with with Broadcast:
  Perfect speedup for arithmetic
  A(myproc) must move to each other processor, costs at least
  (p-1)*cost of sending n*(n/p) words
- Parallel Efficiency = $2*n^3 / (p * \text{Total Time}) = 1/(1 + \alpha * p^2/(2*n^3) + \beta * p/(2*n))$
  $= 1/ (1 + O(p/n))$
  Grows to 1 as n/p increases (or α and β shrink)

MatMul with 2D Layout

- Consider processors in 2D grid (physical or logical)
- Processors can communicate with 4 nearest neighbors
  - Broadcast along rows and columns



Cannon's Algorithm

… $C(i,j) = C(i,j) + \sum_k A(i,k)*B(k,j)$

… assume s = sqrt(p) is an integer

```
forall  i=0 to s-1                …  "skew" A
    left-circular-shift row i of A by i
    … so that A(i,j) overwritten by A(i,(j+i)mod s)
forall  i=0 to s-1                …  "skew" B
    up-circular-shift B column i of B by i
    … so that B(i,j) overwritten by B((i+j)mod s), j)
for k=0 to s-1        … sequential
    forall i=0 to s-1 and j=0 to s-1    … all processors in parallel
        C(i,j) = C(i,j) + A(i,j)*B(i,j)
        left-circular-shift each row of A by 1
        up-circular-shift each row of B by 1
```

Communication in Cannon



C(1,2) = A(1,0) * B(0,2) + A(1,1) * B(1,2) + A(1,2) * B(2,2)

Cost of Cannon's Algorithm

```
forall  i=0 to s-1                    …  recall s = sqrt(p)
    left-circular-shift row i of A by i    … cost = s*(α + β*n^2/p)
forall  i=0 to s-1
    up-circular-shift B column i of B by i … cost = s*(α + β*n^2/p)
for k=0 to s-1
     forall  i=0 to s-1 and j=0 to s-1
         C(i,j) = C(i,j) + A(i,j)*B(i,j)   … cost = 2*(n/s)^3 = 2*n^3/p^(3/2)
         left-circular-shift each row of A by 1   … cost = α + β*n^2/p
         up-circular-shift each row of B by 1     … cost = α + β*n^2/p
```

- Total Time = $2*n^3/p + 4*s*\alpha + 4*\beta*n^2/s$
- Parallel Efficiency = $2*n^3$ / (p * Total Time)
  = $1/(1 + \alpha * 2*(s/n)^3 + \beta * 2*(s/n))$
  = $1/(1 + O(sqrt(p)/n))$
- Grows to 1 as n/s = n/sqrt(p) = sqrt(data per processor) grows
- Better than 1D layout, which had Efficiency = 1/(1 + O(p/n))

Drawbacks to Cannon

- Hard to generalize for
  - p not a perfect square
  - A and B not square
  - Dimensions of A, B not perfectly divisible by s=sqrt(p)
  - A and B not “aligned” in the way they are stored on processors
  - block-cyclic layouts
- Memory hog (extra copies of local matrices)

SUMMA = Scalable Universal Matrix Multiply Algorithm

- Slightly less efficient, but simpler and easier to generalize
- Presentation from van de Geijn and Watts
  - www.netlib.org/lapack/lawns/lawn96.ps
  - Similar ideas appeared many times
- Used in practice in PBLAS = Parallel BLAS
  - www.netlib.org/lapack/lawns/lawn100.ps

SUMMA



- I, J represent all rows, columns owned by a processor
- k is a single row or column (or a block of b rows or columns)
- $C(I,J) = C(I,J) + \Sigma_k A(I,k)*B(k,J)$
- Assume a p_r by p_c processor grid ($p_r = p_c = 4$ above)

```
For k=0 to n-1      … or n/b-1 where b is the block size
                    …  = # cols in A(I,k) and # rows in B(k,J)
    for all I = 1 to p_r   … in parallel
        owner of A(I,k) broadcasts it to whole processor row
    for all J = 1 to p_c   … in parallel
        owner of B(k,J) broadcasts it to whole processor column
    Receive A(I,k) into Acol
    Receive B(k,J) into Brow
    C( myproc , myproc ) = C( myproc , myproc) + Acol * Brow
```

SUMMA performance

```
For k=0 to n/b-1
    for all I = 1 to s   …  s = sqrt(p)
        owner of A(I,k) broadcasts it to whole processor row
            … time = log s *( α + β * b*n/s), using a tree
    for all J = 1 to  s
        owner of B(k,J) broadcasts it to whole processor column
            … time = log s *( α + β * b*n/s), using a tree
    Receive A(I,k) into Acol
    Receive B(k,J) into Brow
    C( myproc , myproc ) = C( myproc , myproc) + Acol * Brow
            … time = 2*(n/s)^2*b
```

- Total time = $2*n^3/p + \alpha * \log p * n/b + \beta * \log p * n^2/s$
- Parallel Efficiency = $1/(1 + \alpha * \log p * p / (2*b*n^2) + \beta * \log p * s/(2*n))$
- ~Same β term as Cannon, except for log p factor
  - log p grows slowly so this is ok
- Latency (α) term can be larger, depending on b
  - When b=1, get $\alpha * \log p * n$
  - As b grows to n/s, term shrinks to $\alpha * \log p * s$ (log p times Cannon)
- Temporary storage grows like 2*b*n/s
- Can change b to tradeoff latency cost with memory

Performance of PBLAS

PDGEMM = PBLAS routine for matrix multiply

Observations:
- For fixed N, as P increases Mflops increases, but less than 100% efficiency
- For fixed P, as N increases, Mflops (efficiency) rises

Speed in Mflops of PDGEMM					
Machine	Procs	Block Size	N		
			2000	4000	10000
Cray T3E	4=2x2	32	1055	1070	0
	16=4x4		3630	4005	4292
	64=8x8		13456	14287	16755
IBM SP2	4	50	755	0	0
	16		2514	2850	0
	64		6205	8709	10774
Intel XP/S MP Paragon	4	32	330	0	0
	16		1233	1281	0
	64		4496	4864	5257
Berkeley NOW	4	32	463	470	0
	32=4x8		2490	2822	3450
	64		4130	5457	6647

DGEMM = BLAS routine for matrix multiply

Maximum speed for PDGEMM = # Procs * speed of DGEMM

Observations (same as above):
- Efficiency always at least 48%
- For fixed N, as P increases, efficiency drops
- For fixed P, as N increases, efficiency increases

Efficiency = MFlops(PDGEMM)/(Procs*MFlops(DGEMM))						
Machine	Peak/ proc	DGEMM Mflops	Procs	N		
				2000	4000	10000
Cray T3E	600	360	4	.73	.74	
			16	.63	.70	.75
			64	.58	.62	.73
IBM SP2	266	200	4	.94		
			16	.79	.89	
			64	.48	.68	.84
Intel XP/S MP Paragon	100	90	4	.92		
			16	.86	.89	
			64	.78	.84	.91
Berkeley NOW	334	129	4	.90	.91	
			32	.60	.68	.84
			64	.50	.66	.81

Summary of Parallel Matrix Multiply Algorithms

° 1D Layout

- Bus without broadcast - slower than serial
- Nearest neighbor communication on a ring (or bus with broadcast): Efficiency = $1/(1 + O(p/n))$

° 2D Layout

- Cannon
  - Efficiency = $1/(1+O(p^{1/2} /n))$
  - Hard to generalize for general p, n, block cyclic, alignment
- SUMMA
  - Efficiency = $1/(1 + O(\log p * p / (b*n^2) + \log p * p^{1/2} /n))$
  - Very General
  - b small => less memory, lower efficiency
  - b large => more memory, high efficiency
- Gustavson et al
  - Efficiency = $1/(1 + O(p^{1/3} /n))$??

Review: BLAS 3 (Blocked) GEPP

```
for   ib = 1 to n-1 step b      … Process matrix b columns at a time
    end = ib + b-1              … Point to end of block of b columns
    apply BLAS2 version of GEPP to  get A(ib:n , ib:end) = P' * L' * U'
    … let LL denote the strict lower triangular part of A(ib:end , ib:end) + I
    A(ib:end , end+1:n) = LL^-1 * A(ib:end , end+1:n)        … update next b rows of U
BLAS 3  A(end+1:n , end+1:n ) = A(end+1:n , end+1:n )
                - A(end+1:n , ib:end) * A(ib:end , end+1:n)
                                  … apply delayed updates with single matrix-multiply
                                  … with inner dimension b
```

Gaussian Elimination using BLAS 3



Review: Row and Column Block Cyclic Layout



4) Row and Column Block Cyclic Layout

processors and matrix blocks are distributed in a 2d array

pcol-fold parallelism in any column, and calls to the BLAS2 and BLAS3 on matrices of size brow-by-bcol

serial bottleneck is eased

need not be symmetric in rows and columns

Distributed GE with a 2D Block Cyclic Layout

block size b in the algorithm and the block sizes brow and bcol in the layout satisfy b=brow=bcol.

shaded regions indicate busy processors or communication performed.

unnecessary to have a barrier between each step of the algorithm, e.g.. step 9, 10, and 11 can be pipelined

Distributed Gaussian Elimination with a 2D Block Cyclic Layout




```
for ib = 1 to n−1 step b

    end = min( ib+b−1, n )

    for i = ib to end

    (1)   find pivot row k, column broadcast

    (2)   swap rows k and i in block column, broadcast row k

    (3)   A( i+1:n , i ) = A( i+1:n , i ) / A( i , i )

    (4)   A( i+1:n , i+1:end) −= A( i+1:n , i ) * A( i , i+1:end )

    end for

(5) broadcast all swap information right and left

(6) apply all rows swaps to other columns
```

(7)



(8)



(9)



(10)



(11)



(7) Broadcast LL right

(8) A(ib:end , end+1:n) = LL \ A(ib:end , end+1:n)

(9) Broadcast A(ib:end , end+1:n) down

(10) Broadcast A(end+1:n , ib:end) right

(11) Eliminate A(end+1:n , end+1:n)

Matrix multiply of green = green - blue * pink

c

Performance of ScaLAPACK LU

PDGESV = ScaLAPACK parallel LU routine

Since it can run no faster than its inner loop (PDGEMM), we measure:
Efficiency = Speed(PDGESV)/Speed(PDGEMM)

Observations:
- Efficiency well above 50% for large enough problems
- For fixed N, as P increases, efficiency decreases (just as for PDGEMM)
- For fixed P, as N increases efficiency increases (just as for PDGEMM)
- From bottom table, cost of solving Ax=b about half of matrix multiply for large enough matrices. From the flop counts we would expect it to be $(2*n^3)/(2/3*n^3) = 3$ times faster, but communication makes it a little slower.

Efficiency = MFlops(PDGESV)/MFlops(PDGEMM)

Machine	Procs	Block Size	N = 2000	N = 4000	N = 10000
Cray T3E	4	32	.67	.82	
	16		.44	.65	.84
	64		.18	.47	.75
IBM SP2	4	50	.56		
	16		.29	.52	
	64		.15	.32	.66
Intel XP/S MP Paragon	4	32	.64		
	16		.37	.66	
	64		.16	.42	.75
Berkeley NOW	4	32	.76		
	32		.38	.62	.71
	64		.28	.54	.69

Time(PDGESV)/Time(PDGEMM)

Machine	Procs	Block Size	N = 2000	N = 4000	N = 10000
Cray T3E	4	32	.50	.40	
	16		.75	.51	.40
	64		1.86	.72	.45
IBM SP2	4	50	.60		
	16		1.16	.64	
	64		2.24	1.03	.51
Intel XP/S GP Paragon	4	32	.52		
	16		.89	.50	
	64		2.08	.79	.44
Berkeley NOW	4	32	.44		
	32		.88	.54	.47
	64		1.18	.62	.49

Demmel Sp 1999

ScaLAPACK SOFTWARE HIERARCHY



LAPACK and ScaLAPACK

	LAPACK	ScaLAPACK
Machines	Workstations, Vector, SMP	Distributed Memory, DSM
Based on	BLAS	BLAS, BLACS
Functionality	Linear Systems Least Squares Eigenproblems	Linear Systems Least Squares Eigenproblems (less than LAPACK)
Matrix types	Dense, band	Dense, band, out-of-core
Error Bounds	Complete	A few
Languages	F77 or C	F77 and C
Interfaces to	C++, F90	HPF
Manual?	Yes	Yes
Where?	www.netlib.org/lapack	www.netlib.org/scalapack

Performance of ScaLAPACK QR (Least squares)

Scales well,
nearly full machine speed

Efficiency = MFlops(PDGELS)/MFlops(PDGEMM)					
Machine	Procs	Block Size	N		
			2000	4000	10000
Cray T3E	4	32	.54	.61	
	16		.46	.55	.60
	64		.26	.47	.54
IBM SP2	4	50	.51		
	16		.29	.51	
	64		.19	.36	.54
Intel XP/S GP Paragon	4	32	.61		
	16		.43	.63	
	64		.22	.48	.62
Berkeley NOW	4	32	.51	.77	
	32		.49	.66	.71
	64		.37	.60	.72

Time(PDGELS)/Time(PDGEMM)					
Machine	Procs	Block Size	N		
			2000	4000	10000
Cray T3E	4	32	1.2	1.1	
	16		1.5	1.2	1.1
	64		2.6	1.4	1.2
IBM SP2	4	50	1.3		
	16		2.3	1.3	
	64		3.6	1.8	1.2
Intel XP/S GP Paragon	4	32	1.1		
	16		1.6	1.1	
	64		3.0	1.4	1.1
Berkeley NOW	4	32	1.3	.9	
	32		1.4	1.0	.9
	64		1.8	1.1	.9

Performance of Symmetric Eigensolvers

Old version,
pre 1998 Gordon Bell Prize

Still have ideas to accelerate
Project Available!

Time(PDSYEVX)/Time(PDGEMM) (bisection + inverse iteration)				
Machine	Procs	Block Size	N 2000	N 4000
Cray T3E	4	32	10	
	16		13	10
	64		29	14
IBB SP2	16	50	24	
	64		40	29
Intel XP/S GP Paragon	16	32	22	
	64		34	20
Berkeley NOW	16	32	20	
	32		24	52

Old Algorithm,
plan to abandon

Time(PDSYEV)/Time(PDGEMM) (QR iteration)				
Machine	Procs	Block Size	N 2000	N 4000
Cray T3E	4	32	35	
	16		37	35
	64		57	41
IBM SP2	16	50	38	
	64		58	47
Intel XP/S GP Paragon	16	32	99	
	64		193	
Berkeley NOW	16	32	31	
	32		35	55

Performance of SVD (Singular Value Decomposition)

Have good ideas to speedup
Project available!

Time(PDGESVD)/Time(PDGEMM)				
Machine	Procs	Block Size	N	
			2000	4000
Cray T3E	4	32	67	
	16		66	64
	64		93	70
IBM SP2	4	50	97	
	16		60	
	64		81	
Berkeley NOW	4	32	72	
	16		38	16
	32		59	26

Performance of Nonsymmetric Eigensolver (QR iteration)

Hardest of all to parallelize
Have alternative, and
would like to compare
Project available!

Time(PDLAHQR)/Time(PDGEMM)				
Machine	Procs	Block Size	N	
			1000	1500
Intel XP/S MP Paragon	16	50	123	97

Out-of-Core Performance Results for Least Squares

- Prototype code for Out-of-Core extension
- Linear solvers based on "Left-looking" variants of LU, QR, and Cholesky factorization
- Portable I/O interface for reading/writing ScaLAPACK matrices

Out-of-core means matrix lives on disk; too big for main mem

Much harder to hide latency of disk

QR much easier than LU because no pivoting needed for QR

Moral: use QR to solve Ax=b

Projects available (perhaps very hard…)



A small software project ...

Participants

Krste Asanovic (UC Berkeley)
Richard Barrett (U. Tenn)
Jeff Bilmes (UC Berkeley)
Susan Blackford (ORNL)
Tony Chan (UCLA)
Jaeyoung Choi (LBNL)
Ed D'Azevedo (ORNL)
Inderjit Dhillon (UC Berkeley)
Jack Dongarra (U Tenn, ORNL)
Jeremy Du Croz (NAG)
Stan Eisenstat (Yale)
John Gilbert (Xerox PARC)
Sven Hammarling (NAG)
Greg Henry (Intel)
Steve Huss-Lederman (SRC)
W. Kahan (UC Berkeley)
Rencang Li (UC Berkeley)
Joseph Liu (York)
Antoine Petitet (U Tenn)
Roldan Pozo (U Tenn)
Huan Ren (UC Berkeley)
Charles Romine (ORNL)
Ivan Slapničar (U Split)
Ken Stanley (UC Berkeley)
Bernard Tourancheau (U Tenn)
Robert van de Geijn (U Texas)
Paul Van Dooren (U Illinois)
David Walker (ORNL)
Kathy Yelick (UC Berkeley)
Zhaojun Bai (U Kentucky)
Michael Berry (U Tenn)
Chris Bischof (ANL)
Soumen Chakrabarti (UC Berkeley)
Chee-Whye Chin (UC Berkeley)
Andy Cleary (LLNL)
Jim Demmel (UC Berkeley)
June Donato (ORNL)
Zlatko Drmač (U Hagen)
Victor Eijkhout (UCLA)
Vince Fernando (NAG)
Ming Gu (UC Berkeley, LBL)
Mike Heath (U Illinois)
Dominic Lam (UC Berkeley)
Bo Kågström (U Umeå)
Youngbae Kim (U Tenn)
Xiaoye Li (UC Berkeley)
Beresford Parlett (UC Berkeley)
Peter Poromaa (U Umeå)
Padma Raghavan (U Illinois)
Howard Robinson (UC Berkeley)
Jeff Rutter (UC Berkeley)
Dan Sorensen (Rice U)
Xiaobai Sun (ANL)
Anna Tsao (SRC)
Henk van der Vorst (Utrecht U)
Krešimir Veselić (U Hagen)
Clint Whaley (U Tenn)

With the cooperation of
Cray, IBM, Convex, DEC, Fujitsu, NEC, NAG, IMSL

Supported by ARPA, NSF, DOE