Berkeley Lab Checkpoint/Restart (BLCR) for Linux Clusters

http://ftg.lbl.gov/checkpoint

checkpoint@lbl.gov

Paul H. Hargrove and Jason C. Duell Lawrence Berkeley National Laboratory

Berkeley Lab Checkpoint/Restart (BLCR for short) is a part of the SciDAC Scalable Systems Software ISIC, with the goal of providing a reusable, production-quality, system-level implementation of Checkpoint/Restart for High Performance Computing on Linux clusters.

Implemented at the system-level

- No source code modifications for most scientific applications
- Recompilation or relinking with a supported MPI may be required
- Permits save/restore of resources not easily accessible from user space

Saves and restores the basic resources

- Virtual address space with file mappings (exec and libs)
- Signal Handlers
- Open files ("by reference" not full content)
- PID and TGID

• Available on x86 and x86-64 architectures

No significant technical barriers to other ports

Available on a wide range of kernels

- Linux 2.4.x and 2.6.x from kernel.org
- SuSE 7.2 through 10.0
- Red Hat 7.1 through 9
- Fedora Core 2 through 4
- Many others
- NO support effort for 2.5.x development kernels

Open Source Software

- Kernel portions under GPL
- User space portions under LGPL

• Implemented as a loadable kernel module

- No kernel patches to void vendor support
- Can more easily track kernel updates

Uses GNU autoconf for wide kernel coverage

- Can check for specific kernel functions and data types • Not dependent on kernel version number, making it tolerant of patches applied by the distribution, vendor or
- Key to supporting Red Hat 9 kernel (a mix of Linux 2.4.x and 2.6.x code)

Integrates GNU autotools with Linux kbuild • configure; make; make install

Preemptive

site.

- Not intended to replace application-level checkpointing when available
- Can be used to respond to fault precursors, such as:
 - High correctable error rates from ECC memory
 - High checksum failures from interconnect
 - Elevated temperature (loss of a fan or chilled water)
- Can be used for preeemption in batch scheduling
 - Higher utilization (no queue draining)
 - Lower wait times (time slice the "wide" jobs)
 - Multiple QoS options

SMP-safe and thread-safe

 Supports both LinuxThreads and NPTL versions of POSIX threads

• Single-node with an extension interface


- Handles most resources within a single Linux kernel instance (see chart at left)
- Allows external support for resources BLCR doesn't save/restore
 - LAM/MPI 7.x uses this interface to provide coordinated checkpointing of MPI jobs and associated socket or gm communications.
 - Support in other MPIs in-progress

Migration-capable (limited)

- No node-specific data required in the checkpoint
- No attempt to hide IP or hostname changes
- MPI support exists in LAM/MPI

No resource virtualization or interception of C-library calls

- BLCR adds absolutely zero code to libc execution paths
- Security-conscious
 - Checkpoint permissions follows that of signals and core dumps
 - Process owner or root required to request a checkpoint
 - Set-id processes may **not** be checkpointed
 - Restart procedure does **not** bypass normal permission checks
 - Modification of a context file will **not** lead to privilege escalation




REFERENCES (Available at http://ftg.lbl.gov/checkpoint)

- Sankaran S, Squyres J M, Barrett B, Lumsdaine A, Duell J, Hargrove P and Roman E 2003 The LAM/MPI checkpoint/restart framework: system-initiated checkpointing *Proc. Los* Alamos Computer Science Institute (LACSI) Symp. (Santa Fe, New Mexico, USA, October 2003)
- Also appearing in 2005 Intl. J. High Performance Computing Applications 19 479-93 • Duell J, Hargrove P and Roman E 2002 Requirements for Linux Checkpoint/Restart *Lawrence* Berkeley National Laboratory Technical Report LBNL-49659
- Duell J, Hargrove P and Roman E 2002 The Design and Implementation of Berkeley Lab's Linux Checkpoint/Restart Lawrence Berkeley National Laboratory Technical Report LBNL-54941
- Roman E 2003 A Survey of Checkpoint/Restart Implementations Lawrence Berkeley National Laboratory Technical Report LBNL-54942

Current Feature Set

Feature	Implemented	Planned	Won't Support
Single-threaded processes	X		
Threaded processes	X		
Process groups		X	
Sessions		X	
Extension API	X		
Signal state/handlers	X		
Restart system calls	X		
Ptraced processes			X
PID & PPID	X		
UID/GID	IFF root		
Resource limits		X	
rusage info		X	
Regular files	X		
Stdin/stdout/stderr	X		
Unnamed & named pipes	X		
TCP/UDP sockets			X
mmapped files	X		
Shared mmap regions		X	
Block device files (/dev/null, /dev/zero, etc)	X		
/proc/self files	X		
File locks		X	
Asynchronous I/O			3
Mprotect() and madvise()	X		
System V IPC			;
Pthread synchronization	X		



Restarting from a Checkpoint

